



- ✓ Standard product, easily available
- ✓ Covers most of homogenization needs
- ✓ Short delivery time

Function :

LUMPP's top-entry mixers without sealing are designed and manufactured to be installed in an open tank with atmospheric pressure and an inside temperature up to 100°C. This range of mixers has been specially designed to cover most of the usual needs in terms of standard agitation and to be able to handle a density up to 1,200 kg/m³ and a viscosity up to 500 cps.

Applications :

- Waste and water treatment
- Final blends: paint, ink, fine polymers
- Reagent preparation: metallurgy, fine chemistry, polymerization
- Food: flavors, syrups, sweets, starch, yeast, amino-acids
- Beverage: wine, beer, alcohol, oil
- Bioenergy: small volumes for fermentation, liquefaction, washing...

Key features :

- Power from 0.18 to 30 kW
- Speed from 1,500 to 10 rpm
- Shaft length up to 6,000 mm
- Available wetted part material: stainless steel, carbon steel, rubber, halar covered, coating, resin...
- ATEX certified
- Impeller diameter up to 3,000 mm
- Equipped with high performance propeller or turbine



Maturation mixers - wastewater treatment

HASLER-GROUP

Headoffice

ZI l'Abbaye - 496 rue Louis Bréguet
38780 Pont-Evêque – France

Tel. +33 (0)4 74 16 11 50

Fax +33 (0)4 74 16 11 55

E-mail: sales.fr@hasler-gp.com

All our addresses on :
www.lumpp.fr